

Rubaroc® Sealer

Rubaroc® Sealer

Section 01 - Chemical and Product and Company Information

Product Identifier Solvent

Product Use Industrial solvent. For industrial use

Supplier Name only. Rubaroc

2416 Wyecroft Rd Unit #3 Oakville, ON L6L 6M6

Prepared by Rubaroc Regulatory Department

Phone: 1 (888) 763-7276

 Preparation Date
 08/15/2018

 Poison Control
 800-268-9017

24-Hour Emergency Phone

613-966-6666

•		•			
Hazardous Ingredient	%	CAS#	LD50 mg/kg ra	t LC50 mg/kg rat	HRS
Pentanedioic acid, dimethyl ester	40-70	1119-40-0	8191 MG/KG	>5.6 MG/L	4
Hexanedioic acid, dimethyl ester	10-30	627-93-0	1920 MG/KG	NOT AVAILABLE	-
Butanedioic acid, dimethyl ester	10-30	106-65-0	>5000 MG/KG	>5000 MG/L	-

Refer to Section 8 for Occupational Exposure Guidelines.

Section 03 - Hazard Identification

Routes of Entry

Eye contactCan cause eye irritation. **Ingestion**Harmful, may enter lungs.

irritation. Can cause temporary blurred vision.

Skin absorption Passage of this material into the body through the skin is possible

and may add to toxic effects from breathing or swallowing.

Skin contact Can cause skin irritation.

Health hazards Signs and symptoms of overexposure to vapours and skin contact

may include temporary blurred vision. Symptoms typically last for

several hours and are not permanent.

Section 04 - First Aid Measures

Eyes	Quickly and gently blot or brush chemical off the face. Immediately
	flush the contaminated eye(s) with lukewarm, gently flowing water
	for 5 minutes, while holding eyelid(s) open. Obtain medical advice.





Rubaroc® Sealer

1	N.I.						
Ingestion		ever give anything by mouth if victim is rapidly losing					
		ciousness or is unconscious or convulsing. Have victim rinse					
		uth thoroughly with water. Do not induce vomiting. Have victim					
	drink	c 60 to 240 ml (2 to 8 oz) of water. If vomiting occurs naturally,					
	have	e victim lean forward to reduce risk of aspiration. Have victim					
	rinse	mouth with water again. If breathing is difficult, trained					
	perso	onnel should administer emergency oxygen. If breathing has					
	stopp	ped, trained personnel should immediately begin artificial					
	respir	ration (AR) or, if the heart has stopped, cardiopulmonary					
	resuso	scitation (CPR) or automated external defibrillation (AED)					
	quickl	ckly transport victim to an emergency care facility.					
Inhalation	Remove source of contamination move victim to fresh air, obtain						
	medic	cal advice.					
Skin (dermal)	Remove contaminated clothing, shoes and leather goods (e.g.						
	watch	watchbands, belts). Quickly and gently, blot or brush away excess					
	chemical. Wash gently and thoroughly with lukewarm gently						
	flowing water and non-abrasive soap for 5 minutes. If irritation						
	persists, repeat flushing. Obtain medical advice. Completely						
	decontaminate clothing, shoes and leather goods before reuse or						
	discar	discard.					
Note to physician	The m	The main hazard following accidental ingestion is aspiration of the					
	liquid	into the lungs producing chemical pneumonitis.					
Section 05 - Fire Fighting							
Flash point(°C)		103°c T.C.C.					
Upper flammable limit (% by	y vol)	8.0%					
Lower flammable limit (% by vol)		0.9%					
Autoignition temperature(°C)		370°C					
Extinguishing media		Foam, water fog, dry chemical, carbon dioxide.					
Special firefighting procedures		Use water spray to cool fire-exposed containers or					
		structures. Product will float and can be reignited on surface					

Unusual fire and explosion hazards No data.

Hazardous combustion products Carbon monoxide and/or carbon dioxide and toxic fumes.

of water. Do not use a direct stream of water as it may

Section 06 - Accidental Release Measures

Spill Ventilate, avoid skin/eye contact; dyke large spills; absorb

spread fire.

according to government regulations



Material Safety Data Sheet

Softroc® Sealer

Section 07 - Handling and Storage

Handling & equipment Use in well ventilated area; ground equipment; use explosion proof

tools and ventilation; keep away from sparks and open

Flames; wash clothing and skin after contact

Storage Store in, well ventilated area at normal ambient temperature

section 8 - personal protection/exposure control

Section 08 - Personal Protection and Exposure Controls

Protective equipment

Gloves Impervious. Butyl rubber.

Respirator Approved organic canister mask or air supplied

Eye Chemical safety goggles/glasses

Footwear Impervious

Clothing Impervious (apron, overalls)
Other Use good personal hygiene

Exposure limits

TLV Not available.
TWA Not available.

Engineering controls

Exhaust Local/mechanical/explosion proof

Section 09 - Physical and Chemical Properties

Physical state Liquid

Appearance & odour Clear, colourless, sweet odour.

Odour threshold 0.1 ppm Boiling point(°C) 196 - 225°C

Freezing point(°C) 20°C

Vapour pressure (mm hg) 0.2 mm hg 20°C

Vapour density (air=1) >1.00

Evaporation rate < 0.10 (n-butyl acetate = 1.0)

Specific gravity 1.092 @ 20°C Solubility in water 5.3% @ 20°C Coeff. Water/oil dist. Not available

Section 10 - Stability and Reactivity

Stability Stable

Incompatibility Strong acids, alkalis, oxidizing agents.

Conditions to avoid Excessive heat/ignition sources

Hazardous decomposition products Carbon monoxide and/or carbon dioxide.



Material Safety Data Sheet

Rubaroc® Sealer

Section 11 - Toxicological Information

Effects of acute exposure

Eyes Irritating. May cause tearing, reddening and/or swelling. Blurred vision.

Ingestion Liquid aspirated into the lungs can cause lung inflammation and lung

injury. And can cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Inhalation Excessive inhalation of vapours can cause nasal and respiratory irritation.

High concentrations may cause shortness of breath (lung edema). Overexposure to high concentrations may cause temporary blurred vision. Symptoms may last for several hours after exposure has stopped. No permanent vision impairment has been reported. Skin absorption

may enhance these effects.

Skin (dermal) May cause irritation. Prolonged and repeated contact can cause

defatting and drying of the skin resulting in irritation and dermatitis. May

be absorbed, blurred vision (temporary) may result from absorption.

Effects of chronic exposure

Carcinogenicity No known human effect.

Reproductive Effects have been reported in animals.

Teratogenicity Not available
Mutagenicity Not available
Synergistic products None known
Other Not available

Section 12 - Ecological Information

Aquatic Toxicity LC50 96H (pimephales promelas) 19.6-26.2 MG/L EST.

(Pentanedioic acid, dimethyl ester)

Environmental Effects prevent from entering drains, sewers, streams or other

bodies of water. If runoff occurs, notify authorities as

required.

Section 13 - Disposal Consideration

Waste Disposal Dispose of in accordance with all federal provincial and

local regulations.

Section 14 - Transportation Information

Proper shipping name (ground only).

Nonregulated TDG classification (ground only)

Nonregulated



Material Safety Data Sheet

Rubaroc® Sealer

Section 15 - Regulatory Information

WHMIS Classification



This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

D2B – Toxic (eye and skin irritant)

Section 16 - Other Information

The information contained in this form is based on data from sources considered to be reliable but Rubaroc®. Does not guarantee the accuracy or completeness thereof. The information is provided as a service to persons purchasing or using the material to which it refers and Rubaroc®. Expressly disclaims all liability for loss or damage, including consequential loss, or for injury to persons (including death) arising directly or indirectly from reliance upon the information or use of the material.